



FILTER GUIDE

F-19

4" x 6.5" | Flow Rate: Up to 50 scfm



WATER	LIQUID HYDROCARBONS	MERCAPTAN	SULFUR H ₂ S	REPLACEMENT CARTRIDGE	FILTER
✓				FE03600	F190A0
	✓	✓		FE04500	F190C0
	✓	✓	✓	FE07900	F190S0

F-4

4.5" x 13" | Flow Rate: Up to 50 scfm



WATER	LIQUID HYDROCARBONS	MERCAPTAN	SULFUR H ₂ S	REPLACEMENT CARTRIDGE	FILTER
✓				FE02000	F04000A
	✓	✓		FE03000	F04000B
✓		✓	✓	FE13800	F04000I

F-5

4.5" x 20" | Flow Rate: Up to 50 scfm



WATER	LIQUID HYDROCARBONS	MERCAPTAN	SULFUR H ₂ S	REPLACEMENT CARTRIDGE	FILTER
✓				FE03100	F05000B
✓	✓	✓		FE02300	F05000A
	✓	✓		FE03700	F05000C
✓		✓	✓	FE09400	F05000HE

MAINTENANCE

Welker recommends that filter cartridges be changed every six months under normal operating conditions.

Some applications may shorten or lengthen the life of the filter cartridge from the suggested six month interval due to the level of severity of the application. Severe service, dirty conditions, excessive usage, or other unique applications may decrease the useful life of the cartridge, so a more frequent maintenance schedule may be appropriate.

SERVICE

We're happy to help! Our factory-trained technicians offer on-site and in-house cartridge replacements. Ensure optimal performance with regularly scheduled cartridge replacements.



281.207.1887

